

EN - A0007365 FALL ARREST HARNESSSES

This product has been designed in compliance with Regulation (EU) 2016/425 and harmonized standard EN 361:2002 and EN 365:2004.

Notified Control Body responsible for the EU Type Exam:
 WUJ a.s., Notified body 1019. Píkartská 1337/7, 716 00 Ostrava, Czech Republic.

Body intervening in the control of production (Module D):
 WUJ a.s., Notified body 1019. Píkartská 1337/7, 716 00 Ostrava, Czech Republic

Important This product must only be used by competent and responsible persons, or those placed under the direct and visual control of a competent and responsible person. Specific training is essential before use. Read this notice carefully and keep all instructions and information on the proper use and field of application of the product(s). Only the techniques shown in the diagrams are authorized. All other uses are excluded: danger of death. Contact L'echelle Europeenne if you have any doubt or difficulty understanding these documents. Activities at height are dangerous and may lead to severe injury or even death. Gaining an adequate apprenticeship in appropriate techniques and methods of protection is your responsibility. Your personally assume all risks and responsibilities for all damage, injury or death which may occur during or following incorrect use of our products in any manner whatsoever. If you are not able, or not in a position to assume this responsibility or to take this risk, do not use this equipment.

VERIFICATION

Before each use, check the webbing at the attachment points, at the adjustment buckles and at the safety stitching. Look for cuts, wear and damage due to use, to heat, and to contact with chemical products, etc... (check for cut or worn threads). Check that the buckles operate correctly. Make sure the body, gate, and locking sleeve are free of any cracks, deformation, corrosion, etc. open the gate and verify that it closes itself automatically when released. Verify that the locking sleeve operates properly. It is important to regularly inspect the condition of the product. Check its connection with the other equipment in the system and make sure that the various pieces of equipment in the system are correctly positioned with respect to each other.

INSTRUCTIONS FOR USE

The A0007365 fall arrest harnesses is personal protective equipment indicated:
 Full body harness for fall arrest: component of a fall arrest system in accordance with EN 363 standard (personal fall arrest systems). It must be used in conjunction with EN 795 anchors, EN 362 locking carabiners, EN 355 energy absorber, etc. To support the body of a conscious person in a sitting position. Before using the equipment, you need to take the necessary measures to rescue the user in a safe manner, if necessary. Verify the compatibility of the harness with the others elements of the fall arrest or work positioning system. The anchor point for the system should be located above the user's position and should meet the requirements of the standard EN 795. Open the buckles on the leg straps on the harness open.
 a. Putting the shoulder straps off the one side, hold the seat harness by the belt, put your legs through the belt and pull it up to your waist.
 b. Adjust the belt by pulling on the belt straps. Stow the excess webbing neatly using the strap retainers (flat against the waist belt).
 c. Fasten and adjust the leg loops.
 d. Position the shoulder straps on the shoulders. Put the connector in the ventral point connecting the chest harness to the seat harness. Lock the connector by turning the locking sleeve.
 e. Adjust the shoulder straps. Stow the excess webbing using the strap retainer on the shoulder strap

2. Fall arrest attachment
2.1 Dorsal fall arrest attachment

2.2 Chest fall arrest attachment
 Use only these points to attach a fall arrest system (for example a mobile fall arrester, an energy absorber, or other systems described in the EN 363 standard). For ease of identification, these points are marked with the letter "A".

3. Compatibility attachment points/connectors

The attachment points of your harness can produce a leverage effect on the gate of the connector. In the case of sudden tension of the rope and/or impact on the carabiner gate, combined with an unfavourable positioning of the carabiner, it is possible for the locking sleeve to break and the gate to open. To reduce the risk, take care that connectors are positioned correctly each time that the system is put under tension (lanyard, descender...). Check also that connectors used are compatible with the attachment points (shapes, dimensions...). For your safety, get into the habit of always doubling up on systems, particularly, carabiners. Set up a second system as a back up for your work positioning system.

LIFETIME

For all equipment with textile or plastic components, the theoretical service life of the equipment is 15 years from the date of manufacture. The service life for metal equipment and parts is indefinite. The actual service life of the equipment will depend on the intensity and frequency of usage, the environment where it is used (contact with chemical and/or corrosive substances, heat, etc.), the user's skill (avoiding abrasion, impact, or cuts), maintenance, storage, etc.

The manufacturer or a competent centre or person must check the equipment at least every 12 months from the date it is put into service. It is recommended to increase the frequency of these checks if usage is intensive. A monitoring sheet where the results can be recorded has been included to better control the equipment. The equipment should be preferably assigned to a single user, who will thus know its history. The inspection should check:

- Fabric: Looking for cuts, wear and damage from use, heat, chemical products, etc.
- Stitching: Looking for broken threads or fraying.
- Buckles: Correct operation.

Whenever the equipment is involved in a fall, impact or working in adverse conditions, it must be inspected for possible damage. This product should not be used again after a significant impact: Internal breakage that is not visibly appreciable could diminish its resistance, limiting its protective function.

L'echelle europeene reserves the right to approve checks made by third parties, even if they have participated in our training programmes. In case of doubt, please contact L'echelle europeene

CLEANING, DISINFECTION AND STORAGE


Keep your harness in a bag or other container to protect it from exposure to UV, moisture, chemical products, etc. A dirty product should be cleaned, by hand, on a delicate material wash and rinsed in clean water (maximum temperature 30° C). Then dried in a cool, ventilated, dark room. Grease spots may be removed with trichloroethylene. Webbing which has been wetted, then dried, shrinks very slightly. All chemical products, corrosive materials and solvents should be regarded as harmful. If it is absolutely necessary, or if there is a risk of contact with chemical products, please contact us, stating the precise name of the chemicals concerned. Alter study we will give you an appropriate reply. If it is necessary to disinfect the product, use a disinfectant that is compatible with polyamide, polyester, polycarbonate, PVC etc. Use in a solution diluted with clean water at a maximum temperature of 20° C. Allow to soak for an hour, then rinse in clean cold water. Dry slowly, away from direct heat sources. Always carry and store a product in its bag. Despite its UV protection it is recommended that this product is stored away from direct light, in a well ventilated place away from extreme temperatures. Check that it is not too crumpled or screwed up.

MARKING

The product is marked with:
 Manufacturer: Productos Climax, S.A
 Model: A0007365
 Norm: EN 361-2002
 Manufacturing date: see picture
 Certification and body controlling the manufacturing of this PPE: CE 1019
 Batch n°:

PRECAUTIONS

Do not allow this product to rub against abrasive materials or sharp edges. Users must be medically fit for activities at height. Inert suspension in a harness can result in serious injury or death. You must check to ensure that the product markings remain legible during the entire lifetime of the product. You must verify the suitability of this equipment for use in your application with regard to applicable governmental regulations and other standards on occupational safety. The instructions of use for each item of equipment used in conjunction with this product must be respected For user safety, it is essential that if the product is re-sold outside the original country of destination, it must be accompanied with instructions for use, maintenance, regular checks and repairs in the language of the country where the equipment is to be used.



ARNÉS ANTICAÍDAS MOD. A0007365 A0007365 FALL ARREST HARNESSSES	Nombre del usuario / User's name	Fecha de compra / Date of purchase	Fecha puesta en servicio / Date first used	Nº lote / Batch number	Comentarios / Remarks	Firma responsable / Signature												
						Responsible Revision / Responsible for check												
						Fecha Revisión / Inspection date												

- FR **NOMENCLATURE DES PARTIES**
 1. Point d'ancrage anti-chutes dorsal
 2. Point d'ancrage anti-chutes sternal
- ES **NOMENCLATURA DE LAS PARTES**
 1. Punto de enganche anticaídas dorsal
 2. Punto de enganche anticaídas esternal
- EN **NOMENCLAURE OF PARTS**
 1. Dorsal fall arrest attachment point (EN 361)
 2. Chest fall arrest attachment point (EN 361)
- NL **TERMINOLOGIE ONDERDELEN**
 1. Bevestigingspunt voor valbeveiliging met rugbevestiging
 2. Bevestigingspunt voor valbeveiliging met borstbevestiging